

Please compose your personal Trimobil and fill in the order form. Just send us by mail or fax: 0049-4127-922-84):

Mail to:

**Toxy Liegerad GmbH**  
**Recumbents & Components**  
**Steinstr. 5**  
**D - 25364 Hörnerkirchen**  
**Germany**

**Yes, I order the items above. I want to prepay the goods**

by cheque / cash

by bank transfer

**Riders size** (appr.) : \_\_\_\_\_ ft/cm (passenger): \_\_\_\_\_ ft/cm

**My stile of riding:**  often with 0 1 /  2 passenger(s)  
 often with load > 220lbs/100kgs

(Necessary for correct seat size, and pre-adjustment of components.)

**My address** (please also delivery address, if different):

\_\_\_\_\_  
 (company / first name; name)

\_\_\_\_\_  
 (street; no.)

\_\_\_\_\_  
 (city / country)

\_\_\_\_\_  
 (date)

\_\_\_\_\_  
 (signature)

\_\_\_\_\_  
 (e-mail)

\_\_\_\_\_  
 (tel.-no.)

### Trimobil serial assembly

**Options** (pls. see orderform)

<b>Main frame</b>	Steel/stainless steel, reinforced; powder coated in standard colours white, red or black	Custom colours according to RAL
<b>Front frame</b>	Reinforced alloy-frame, black powdercoating one-size-fits-all from 5ft to 7,5ft length	
<b>Drive fork</b>	Trimobil Front drive fork, steel/CrMo 1 1/8"; black powdercoating	
<b>Light system</b>	„Busch & Müller“ LED lights front & rear, with dynamo hub	SON dynamo hub incl. "Edelux"
<b>Tires</b>	Schwalbe „Marathon plus“ 47-406 (reflex)	„Marathon Winter“ 42-406 (Spike)
<b>Breaks</b>	Rear: 2x hydraulic disc break „Magura“ with 203mm disc Front: Mech. parking break	
<b>Rider seat</b>	Glass-fibre ergo-seat; adjustable seat hight, angle & position Including airflow comfort seat cushion (removable & washable at 30°)	2 passenger seats (as rider seat) 2 baby seats incl. fixation bar
<b>Rims</b>	20" (406), alloy hollow chamber with stainless spokes At rear wheels including black wheel covers for your advertising	
<b>Chain</b>	SRAM PC with „Power-Link“; covered with extremely durable chain tubes	
<b>Crankset</b>	Alloy, including chainguards; chainwheels replaceable; hole diameter: 130mm	2nd rear drive unit at left side
<b>Steering</b>	Alloy bar end steering with multi position ergo-adjustment	
<b>Hubs</b>	Alloy disk break hubs, sealed (or internal drive hubs as ordered) Rear right wheel: SRAM or Shimano dynamo hub with disc break mount	Pedelec E-hub motor unit
<b>Pedals</b>	ATB; Alloy, sealed	Clipless or anatomic pedals
<b>Shifters</b>	Twist shifters	
<b>Other basics</b>	Basic assembly including mudguards, rear luggage plate, light system and coupling mount for regular child- & luggage-trailer couplings	Many sales & service options Marketing accessories

Components may vary due to our suppliers.

### Trimobil specification

**comment**

<b>Wheel size front &amp; rear</b>	20" (406)	...absolutely practical, rigid & compact
<b>Over all length</b>	80" - 98" (200 - 245cm)	...shorter than most common tandem
<b>Over all width</b>	37.5" (95cm)	...allowed on bicycle paths (acc. to country)
<b>Over all hight</b>	43" - 70" (110 - 180cm)	...depending on seat adjustment & options
<b>Hight without seat</b>	31.5" (80cm)	...fits into most vans
<b>Parking space, upright</b>	4' x 3.3' (120 x 100cm)	...minimized parking/storage space
<b>Transportation size</b>	59" x 37.5" x 21.5" (150 x 95 x 55cm)	...unique compact & transportable size
<b>Seat hight</b>	pilot: 23.5" - 25.5" (60 - 65cm)   passengers: 21.5" - 23.5" (55 - 60cm)	...depending on indiv. adjustment
<b>Seat angle</b>	39° - 55°	...allows personal adjustment
<b>Bottom bracket hight</b>	pilot: 27.5" (70 cm)   passenger/stoker: 14" (35 cm)	...efficient pedeling
<b>Weight</b>	from 88 lbs (39 kg)	for basic model
<b>Max weight (incl. rider)</b>	660 lbs (300 kg)   passengers each 220 lbs (100 kg)	luggage plates each up to 100 kg
<b>Luggage plate sizes</b>	rear: 23.5" x 23.5" (60 x 60 cm)   front: r. & l., 31.5" x 12.5" (80x32cm)	plates optional; according to requirements
<b>Riders hight range</b>	pilot: 60" - 80" (1,55 - 2,05m)   passengers: 53" - 77" (1,35 - 1,95 m)	crankset & seat adjustment
<b>Baby seats</b>	max. 4; max. weight each 48.5 lbs (22 kg)	additionally just add your bicycle trailer.

All data approx. due to different adjustment & assembly options. Components & assembly may deviate from pictures and descriptions due to manufacturers and technical progress.