

Please compose your personal Trimobil and fill in the order form. Just send us by mail (or fax 0049-4822-9457-413):

Mail to:

Toxy Liegerad GmbH
Recumbents & Components
Bokeler Str. 3
D - 25563 Wrist / Holstein
Germany

Yes, I order the items above. I want to prepay the goods

by cheque / cash

by bank transfer

Riders size (appr.) : _____ ft/cm (passenger): _____ ft/cm

My stile of riding: often with 1 / 2 passenger(s)
 often with load > 220lbs/100kgs

(Necessary for correct seat size, and pre-adjustment of components.)

My address (please also delivery address, if different):

_____ (company / first name; name)

_____ (street; no.)

_____ (city / country)

_____ (date) _____ (signature)

_____ (e-mail)

_____ (tel.-no.)

Trimobil serial assembly

Options (pls. see orderform)

Main frame	Steel/stainless steel, reinforced; powder coated in standard colours white, red or black	Custom colours according to RAL
Front frame	Reinforced alloy-frame, black powdercoating one-size-fits-all from 5ft to 7,5ft length	
Drive fork	Trimobil Front drive fork, steel/CrMo 1 1/8"; black powdercoating	
Light system	„Busch & Müller“ LED lights front & 2x rear, with dynamo hub	SON dynamo hub incl. "Edelux"
Tires	Schwalbe „Marathon plus“ 47-406 (reflex)	„Marathon Winter“ 42-406 (Spike)
Breaks	Rear: 2x hydraulic disc break „Magura MT“ with 203mm disc Front: Mech. parking break	
Rider seat	Glass-fibre ergo-seat; adjustable seat hight, angle & position Including airflow comfort seat cushion (removable & washable at 30°)	2 passenger seats (as rider seat) 2 baby seats incl. fixation bar
Rims	20" (406), alloy hollow chamber with stainless spokes At rear wheels including black wheel covers for your advertising	
Chain	SRAM PC with „Power-Link“; covered with extremely durable chain tubes	
Crankset	Alloy, including chainguards; chainwheels replaceable; hole diameter: 130mm	2nd rear drive unit at left side
Steering	Alloy bar end steering with multi position ergo-adjustment	
Hubs	Alloy disk break hubs, sealed (or internal drive hubs as ordered) Rear right wheel: SRAM or Shimano dynamo hub with disc break mount	Pedelec E-hub motor unit
Pedals	ATB; Alloy, sealed	Clipless or anatomic pedals
Shifters	Twist shifters	
Other basics	Basic assembly including mudguards, rear luggage plate, light system and coupling mount for regular child- & luggage-trailer couplings	Many sales & service options Marketing accessories

Components may vary due to our suppliers.

Trimobil specification

comment

Wheel size front & rear	20" (406)	...absolutely practical, rigid & compact
Over all length	80" - 98" (200 - 245cm)	...shorter than most common tandem
Over all width	37.5" (95cm)	...allowed on bicycle paths (acc. to country)
Over all hight	43" - 70" (110 - 180cm)	...depending on seat adjustment & options
Hight without seat	31.5" (80cm)	...fits into most vans
Parking space, upright	4' x 3.3' (120 x 100cm)	...minimized parking/storage space
Transportation size	59" x 37.5" x 21.5" (150 x 95 x 55cm)	...unique compact & transportable size
Seat hight	pilot: 23.5" - 25.5" (60 - 65cm) passengers: 21.5" - 23.5" (55 - 60cm)	...depending on indiv. adjustment
Seat angle	39° - 55°	...allows personal adjustment
Bottom bracket hight	pilot: 27.5" (70 cm) passenger/stoker: 14" (35 cm)	...efficient pedeling
Weight	from 88 lbs (39 kg)	for basic model
Max weight (incl. rider)	660 lbs (300 kg) passengers each 220 lbs (100 kg)	luggage plates each up to 100 kg
Luggage plate sizes	rear: 23.5" x 23.5" (60 x 60 cm) front: r. & l., 31.5" x 12.5" (80x32cm)	plates optional; according to requirements
Riders hight range	pilot: 60" - 80" (1,55 - 2,05m) passengers: 53" - 77" (1,35 - 1,95 m)	crankset & seat adjustment
Baby seats	max. 4; max. weight each 48.5 lbs (22 kg)	additionally just add your bicycle trailer.

All data approx. due to different adjustment & assembly options. Components & assembly may deviate from pictures and descriptions due to manufacturers and technical progress.